

LABOR SRB

VINOGRADARSKA 6,
22000 SREMSKA MITROVICA
PIB: 108704640 - MATIČNI BROJ: 21051195
TEKUĆI RAČUN: 170-30022426000-94
IBAN: RS35170003002242632007 - EUR
SWIFT: BACXRSBG
TELEFON / FAX: +381 (0)22 617 - 397



MULTILAYER PARQUET



18

According to the REGULATION (EU) No 305/2011

Sastav: Hrastov masiv sa vlagootpornom višeslojnom podlogom (šperploča) - 100% drvo.

Primena: Za oblaganje svih vrsta podova u stambenim i poslovnim objektima i na podlogama sa podnim grejanjem.

Postavljanje: Lepljenjem 2K lepkom na betonsku košuljicu max.vlažnosti 2%, moguća postavka i bez lepljenja – plivajući pod.

Skladištenje: Na suvom mestu u originalnom pakovanju do postavke.

Upozorenje: Bez opasnosti po zdravlje, u potpunosti bezbedan ekološki proizvod - fitopatološki nalaz ispravan i zadovoljen

Manufacturer's name: Labor SRB d.o.o.

Manufacturer's address: Vinogradarska 6 22000 Sremska Mitrovica, , Srbija, tel. +381(0)22617397, www.laborsrb.com

The unique identification code of the product-type: Multilayer parquet, acc. to EN 13489:2017

The reference number of the Declaration of performance:

The harmonized technical specification applied: In compliance to the Certificates acc. to EN 14342:2013

Declared performance:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
Reaction to fire, regarding:	Dfl-s1	EN 14342:2013
-minimum average density	500 kg/m ³	
-minimum total thickness	15mm	
-the end-use condition for use	with or without air space below	
Release of formaldehyde	E1	
Content of pentachlorophenol	< 5 ppm	
Release of other hazardous substances	0,02 ppm	
Resistance to fracture	NPD	
Slipperiness	NPD	
Thermal conductivity	0,14 W/m K	
Biological durability	Class 1	

termičkom obradom na 85°C.

Napomena: Čuvati od mehaničkog oštećenja! Garancija za fitopatološku ispravnost neograničena.

Održavanje: Isključivo sredstvima na prirodnoj bazi.

MULTILAYER PARQUET

Composition: Oak massif with moisture bark multipole substrate - 100% wood.

Application: For the coating of all types of floors in residential and commercial buildings and underfloor heating.

Setting: 2K adhesive bonding on concrete jacket with 2% moisture content, possible setting and without adhesion - floating floor.

Storage: In a dry place in the original package to the item.

Warning: No health hazard, fully safe ecological product - phytopathological finding is correct and satisfied by thermal treatment at 85 ° C

Note: Keep away from mechanical damage! Guarantee for phytopathological safety is unlimited.

Maintenance: Exclusively with natural resources.



The mark of
responsible forestry
FSC® C134957

FSC® CERTIFICATE CODE:
ICILA-COC-003030

ONLY THE PRODUCTS
THAT ARE IDENTIFIED AS
SUCH ON THIS DOCUMENT
ARE FSC® CERTIFIED